

Contact: John Wong

211 Yacht Club Way

Redondo Beach, CA 90277

Virina Steel

Element Materials Technology 15062 Bolsa Chica Huntington Beach, CA 92649-1023 USA

P 714 892 1961 F 714 892 8159 T 888 786 7555 info.hb@element.com element.com

TEST CERTIFICATE — EAR-CONTROLLED DATA

Date: Purchase Order Number: Work Order Number

7/18/2019 VERBAL VIR004-06-11-27129-1

Specification:	ASTM A1035-16b GR. 130
Description:	Re-Bar (10x60mm)

REBAR TENSILE							
Test Method: ASTM A370-18							
Requirement: INFO ONLY							
Sample Number	Area	Bar Size	UTS (PSI / LBS)	Yield (PSI / LBS)	8 inch Elongation In %		
1	.2000	4	140,000 / 28,096	103,000 / 20,669	7.0		

BEND TEST

Test Method: ASTM E 290-14 Material Diameter: 0.500" Bend Factor 3.5 Mandrel Diameter: 1.750" Bend Angle: 180° Without cracking on the outside radius of the bent portion. (1) ACCEPTABLE

CONFORMS TO REQUIREMENTS

This document contains technical data whose export and re-export/ retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or reexport/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

Respectfully submitted

nli Kelly Nguyen

Senior Quality Administrator

15062 Bolsa Chica, Huntington Beach, CA 92649

(714) 892-1961 ph • (714) 892-8159 fax www.element.com

Denotes non-conforming results. *Denotes change made from original test certificate. The information contained in this certification represents only the material submitted and is certified only for the quantities tested. Reproduction except in full is reserved pending written approval. The recording of false, fictitious, or fraudulent statements or entries on the certificate may be punishable as a felony under federal law. All testing was performed in a mercury free environment. All testing performed in accordance with the latest edition of the applicable ASTM, or other Federal Test Method in effect at the time of test.